
GAM RUN 22-006: BARTON SPRINGS/EDWARDS AQUIFER CONSERVATION DISTRICT MANAGEMENT PLAN

Shirley Wade, Ph.D., P.G.
Texas Water Development Board
Groundwater Division
Groundwater Modeling Department
(512) 936-0883
March 28, 2022



shirley.c.wade
3/28/22

This page is intentionally blank

GAM RUN 22-006: BARTON SPRINGS/EDWARDS AQUIFER CONSERVATION DISTRICT MANAGEMENT PLAN

Shirley Wade, Ph.D., P.G.
Texas Water Development Board
Groundwater Division
Groundwater Modeling Department
(512) 936-0883
March 28, 2022

EXECUTIVE SUMMARY:

Texas State Water Code, Section 36.1071, Subsection (h) (Texas Water Code, 2011), states that, in developing its groundwater management plan, a groundwater conservation district shall use groundwater availability modeling information provided by the Executive Administrator of the Texas Water Development Board (TWDB) in conjunction with any available site-specific information provided by the district for review and comment to the Executive Administrator.

The TWDB provides data and information to the Barton Springs/Edwards Aquifer Conservation District in two parts. Part 1 is the Estimated Historical Water Use/State Water Plan dataset report, which will be provided to you separately by the TWDB Groundwater Technical Assistance Department. Please direct questions about the water data report to Mr. Stephen Allen at 512-463-7317 or stephen.allen@twdb.texas.gov. Part 2 is the required groundwater availability modeling information, and this information includes:

1. the annual amount of recharge from precipitation, if any, to the groundwater resources within the district;
2. for each aquifer within the district, the annual volume of water that discharges from the aquifer to springs and any surface-water bodies, including lakes, streams, and rivers; and
3. the annual volume of flow into and out of the district within each aquifer and between aquifers in the district.

The groundwater management plan for the Barton Springs/Edwards Aquifer Conservation District should be adopted by the district on or before August 23, 2022 and submitted to the executive administrator of the TWDB on or before September 22, 2022. The current management plan for the Barton Springs/Edwards Aquifer Conservation District expires on November 21, 2022.

We used the groundwater availability model for the Barton Springs segment of the Edwards (Balcones Fault Zone) Aquifer (Scanlon and others, 2001) to estimate the management plan information for the Edwards (Balcones Fault Zone) Aquifer within the Barton Springs/Edwards Aquifer Conservation District. This report provides supplemental information to the results of GAM Run 08-37 (Oliver, 2008) which used the same model. However, the results in GAM Run 08-37 were based on the steady-state model while results for this analysis are based on the transient model covering the period 1989 through 1998. Additionally, the approach used for analyzing model results is reviewed during each GAM Run report update and may have been refined to better delineate groundwater flows. This report also includes a new figure not included in the previous report to help groundwater conservation districts better visualize water budget components. Table 1 summarizes the groundwater availability model data required by statute and Figure 1 shows the area of the model from which the values in Table 1 were extracted. Figure 2 provides a generalized diagram of the groundwater flow components provided in Table 1. If, after review of the figures, the Barton Springs/Edwards Aquifer Conservation District determines that the district boundaries used in the assessment do not reflect current conditions, please notify the TWDB at your earliest convenience.

METHODS:

In accordance with the provisions of the Texas State Water Code, Section 36.1071, Subsection (h), the groundwater availability model mentioned above was used to estimate information for the Barton Springs/Edwards Aquifer Conservation District management plan. Water budgets were extracted for the historical model period for the Edwards (Balcones Fault Zone) Aquifer (1989 through 1999) using ZONEBUDGET Version 3.01 (Harbaugh, 2009). The average annual water budget values for recharge, surface-water outflow, inflow to the district, outflow from the district, and the flow between aquifers within the district are summarized in this report.

PARAMETERS AND ASSUMPTIONS:

Edwards (Balcones Fault Zone) Aquifer

- We used version 1.01 of the groundwater availability model for the Barton Springs segment of the Edwards (Balcones Fault Zone) Aquifer. See Scanlon and others (2001) for assumptions and limitations of the groundwater availability model.
- The groundwater availability model for the Barton Springs segment of the Edwards (Balcones Fault Zone) Aquifer is a one-layer model and assumes no interaction with the underlying Trinity Aquifer. The model grid is relatively fine with grid cells that are 1,000 feet long parallel to the strike of the faults and 500 feet wide.
- The model was run with MODFLOW-96 (Harbaugh and McDonald, 1996).

RESULTS:

A groundwater budget summarizes the amount of water entering and leaving the aquifer according to the groundwater availability model. Selected groundwater budget components listed below were extracted from the groundwater availability model results for the Edwards (Balcones Fault Zone) Aquifer located within the Barton Springs/Edwards Aquifer Conservation District and averaged over the historical calibration period, as shown in Table 1.

1. Precipitation recharge—the areally distributed recharge sourced from precipitation falling on the outcrop areas of the aquifers (where the aquifer is exposed at land surface) within the district.
2. Surface-water outflow—the total water discharging from the aquifer (outflow) to surface-water features such as streams, reservoirs, and springs.
3. Flow into and out of district—the lateral flow within the aquifer between the district and adjacent counties.
4. Flow between aquifers—the net vertical flow between the aquifer and adjacent aquifers or confining units. This flow is controlled by the relative water levels in each aquifer and aquifer properties of each aquifer or confining unit that define the amount of leakage that occurs.


The information needed for the district's management plan is summarized in Table 1. It is important to note that sub-regional water budgets are not exact. This is due to the size of

the model cells and the approach used to extract data from the model. To avoid double accounting, a model cell that straddles a political boundary, such as a district or county boundary, is assigned to one side of the boundary based on the location of the centroid of the model cell. For example, if a cell contains two counties, the cell is assigned to the county where the centroid of the cell is located.

TABLE 1: SUMMARIZED INFORMATION FOR THE EDWARDS (BALCONES FAULT ZONE) AQUIFER THAT IS NEEDED FOR THE BARTON SPRINGS/EDWARDS AQUIFER CONSERVATION DISTRICT’S GROUNDWATER MANAGEMENT PLAN. ALL VALUES ARE REPORTED IN ACRE-FEET PER YEAR AND ROUNDED TO THE NEAREST 1 ACRE-FOOT.


Management Plan requirement	Aquifer or confining unit	Results
Estimated annual amount of recharge from precipitation to the district	Edwards (Balcones Fault Zone) Aquifer	58,712
Estimated annual volume of water that discharges from the aquifer to springs and any surface water body including lakes, streams, and rivers.	Edwards (Balcones Fault Zone) Aquifer	52,212
Estimated annual volume of flow into the district within each aquifer in the district	Edwards (Balcones Fault Zone) Aquifer	3,800
Estimated annual volume of flow out of the district within each aquifer in the district	Edwards (Balcones Fault Zone) Aquifer	3,300
Estimated net annual volume of flow between each aquifer in the district	Flow between the Edwards (Balcones Fault Zone) Aquifer and Underlying Units	Not Applicable ¹

¹ Not applicable because the model assumes a no flow barrier at the base of the Edwards (Balcones Fault Zone) Aquifer



gcd boundaries date = 06.26.2020, county boundaries date = 07.03.2019, ebfz_b grid date = 01.06.2020

FIGURE 1: AREA OF THE GROUNDWATER AVAILABILITY MODEL FOR THE BARTON SPRINGS SEGMENT OF THE EDWARDS (BALCONES FAULT ZONE) AQUIFER FROM WHICH THE INFORMATION IN TABLE 1 WAS EXTRACTED (THE EDWARDS [BALCONES FAULT ZONE] AQUIFER EXTENT WITHIN THE DISTRICT BOUNDARY).



*The groundwater availability model for the Gulf Coast Aquifer System assumes a no-flow condition at the base.

Caveat: This diagram only includes the water budget items provided in Table 1. A complete water budget would include additional inflows and outflows. If the District requires values for additional water budget items, please contact TWDB.

FIGURE 2: GENERALIZED DIAGRAM OF THE SUMMARIZED BUDGET INFORMATION FROM TABLE 1, REPRESENTING DIRECTIONS OF FLOW FOR THE EDWARDS (BALCONES FAULT ZONE) AQUIFER WITHIN BARTON SPRINGS/EDWARDS AQUIFER CONSERVATION DISTRICT. FLOW VALUES EXPRESSED IN ACRE-FEET PER YEAR (AFY).

LIMITATIONS:

The groundwater models used in completing this analysis are the best available scientific tools that can be used to meet the stated objectives. To the extent that this analysis will be used for planning purposes and/or regulatory purposes related to pumping in the past and into the future, it is important to recognize the assumptions and limitations associated with the use of the results. In reviewing the use of models in environmental regulatory decision making, the National Research Council (2007) noted:

“Models will always be constrained by computational limitations, assumptions, and knowledge gaps. They can best be viewed as tools to help inform decisions rather than as machines to generate truth or make decisions. Scientific advances will never make it possible to build a perfect model that accounts for every aspect of reality or to prove that a given model is correct in all respects for a particular regulatory application. These characteristics make evaluation of a regulatory model more complex than solely a comparison of measurement data with model results.”

A key aspect of using the groundwater model to evaluate historic groundwater flow conditions includes the assumptions about the location in the aquifer where historic pumping was placed. Understanding the amount and location of historical pumping is as important as evaluating the volume of groundwater flow into and out of the district, between aquifers within the district (as applicable), interactions with surface water (as applicable), recharge to the aquifer system (as applicable), and other metrics that describe the impacts of that pumping. In addition, assumptions regarding precipitation, recharge, and interaction with streams are specific to particular historic time periods.

Because the application of the groundwater models was designed to address regional scale questions, the results are most effective on a regional scale. The TWDB makes no warranties or representations related to the actual conditions of any aquifer at a particular location or at a particular time.

It is important for groundwater conservation districts to monitor groundwater pumping and overall conditions of the aquifer. Because of the limitations of the groundwater model and the assumptions in this analysis, it is important that the groundwater conservation districts work with the TWDB to refine this analysis in the future given the reality of how the aquifer responds to the actual amount and location of pumping now and in the future. Historic precipitation patterns also need to be placed in context as future climatic conditions, such as dry and wet year precipitation patterns, may differ and affect groundwater flow conditions.

REFERENCES:

Harbaugh, A. W., 2009, Zonebudget Version 3.01, A computer program for computing subregional water budgets for MODFLOW ground-water flow models, U.S. Geological Survey Groundwater Software.

Harbaugh, A. W., and McDonald, M. G., 1996, User's documentation for MODFLOW-96, an update to the U.S. Geological Survey modular finite-difference groundwater-water flow model: U.S. Geological Survey Open-File Report 96-485, 56 p.

Oliver, W., 2008, GAM Run 08-37: Texas Water Development Board, GAM Run 08-37 Report, 4 p., <http://www.twdb.texas.gov/groundwater/docs/GAMruns/GR08-37.pdf>

National Research Council, 2007, Models in Environmental Regulatory Decision Making Committee on Models in the Regulatory Decision Process, National Academies Press, Washington D.C., 287 p., http://www.nap.edu/catalog.php?record_id=11972.

Scanlon, B., Mace, R., Smith, B., Hovorka, S., Dutton, A., and Reedy, R., 2001, Groundwater Availability of the Barton Springs Segment of the Edwards Aquifer, Texas— Numerical Simulations through 2050: The University of Texas at Austin, Bureau of Economic Geology, final report prepared for the Lower Colorado River Authority, under contract no. UTA99-0.

Texas Water Code, 2011, <http://www.statutes.legis.state.tx.us/docs/WA/pdf/WA.36.pdf>